



## PURPOSE

PRESTIGE BONDING Additive is a latex based liquid, specially formulated to be used in conjunction with PRESTIGE CEMENT-BASED Adhesive and PRESTIGE TILE GROUT where complicated application, high traffic areas, permanently wet conditions exist, or where additional flexibility or increased bond strength is required. PRESTIGE BONDING Additive is also a primer for the sealing and stabilising of friable and chalking surfaces, both interior and exterior prior to tiling or coating.

## SURFACE PREPARATION

1. Surfaces must be solid/firm and free of dust, mould oil, grease, wax polish, sealants, and organic growth. Organic growth must be removed and the spores killed with an effective fungicide such as a household bleaching solution.
2. Painted and Gypsum-plastered surfaces need to be chipped to remove 80% of the paint or Gypsum.
3. Enamel-painted and bitumen surfaces: Strip all of the coating by scraping and then chip to expose 80% of the substrate. **DO NOT USE A SOLVENT OR HEAT TO REMOVE BITUMEN FROM THE SUBSTRATE.**
4. Smooth, off-form/shutter or power-floated concrete surfaces: Acid wash to remove laitance, rinse well with cold clean water.

## APPLICATION SHAKE WELL BEFORE USE

1. Replace water in the mix with PRESTIGE BONDING Additive when using PRESTIGE CEMENT-BASED Adhesives and PRESTIGE STANDARD TILE GROUT in the following areas: Heavy duty environments, permanently wet areas, abattoirs, breweries, hospitals, dairies, smooth trowelled wall and floor areas, cold rooms and walls where temperature changes are experienced.
2. PRESTIGE BONDING Additive can also be used as a priming/sealing coat for Gypsum, asbestos and cement surfaces. When used as a primer/sealer, brush on PRESTIGE BONDING Additive until surface is saturated. Leave to dry for a minimum of 1 hour and a maximum of 48 hours before tiling or coating.



## CURING

No curing is required.

NOTE: Cement or cement-based adhesives and grouts will dry a shade darker with the addition of PRESTIGE BONDING Additive. These products will also take approximately 12 hours longer to dry.

## COVERAGE

Refer to application product used along with PRESTIGE BONDING Additive. When used as a primer/sealer, 5 litres PRESTIGE BONDING Additive will cover approximately 25-30m, depending on the nature of the surface. (1 Coat application).

## GUARANTEE

We guarantee that PRESTIGE products meet the product specifications and will be free from any defect. Any guarantee with regard to the performance of PRESTIGE products will be subject to the professional and practical application of PRESTIGE products in accordance with our instructions and specifications.

However, we have no influence over specific site conditions and therefore, if in doubt, the user should first carry out sufficient tests to ensure that the product is suitable. In special cases, obtain advice. Should our product prove defective, we undertake to replace any defective material.

This guarantee will fall away in the event of PRESTIGE products being contaminated or adulterated by the addition of sand, cement or any substance other than recommended by us.

## WARNING

- Do not ingest.
- Keep away from children and pets.
- Do not empty into drains.

## PRECAUTIONS

- Wear rubber gloves.
- Do not ingest.
- In the event of contamination rinse thoroughly with cold water.
- Use as directed.
- Use a dust mask.
- Work in well ventilated areas.
- Seek medical assistance if irritation or discomfort persists.

## PACKAGING

Supplied in:

1lt bottles;

5lt bottles;

20lt drums; and

200lt drums.

---

**TECHNICAL ADVICE CENTRES:**  
Tel: 011 316 3787 • Fax: 011 316 3799  
E-mail: [orders@prestigeadhesives.co.za](mailto:orders@prestigeadhesives.co.za)  
Prestige Adhesives Cape (Pty) Ltd  
Tel: 021 9330334 • Fax: 021 9310969  
E-mail: [orders@prestigecape.co.za](mailto:orders@prestigecape.co.za)

---